Technical specifications

WEIGHT - ECO-PERFORMANCE

Weight	80 kg

DIMENSIONS

Length	205 cm
Width	73 / 84 with option centralized brake system cm
Length sleeping surface	200 cm
Width sleeping surface	65 cm
Variable height minimum	With castors diameter 125 mm: 47 / With castors diameter 150 mm: 49 cm
Variable height maximum	With castors diameter 125 mm: 87 / With castors diameter 150 mm: 89 cm
Ground Clearance	2,3 (castor diameter 125 mm) / 4,1 (castor diameter 150 mm) cm
Dimensions (cm)	Backrest 65 x 69 cm cm
Mattress thickness	6,5 (5 cm foam + 1,5 cm wood) cm

LYING SURFACE

Lying surface - Material	Resilience foam on wooden base

MATERIAL & COATING

Material Foam	Resilience foam
Foam HR density	35 kg/m3
Material Cover	Seamless finish, vinyl coating antibacterial
Frame	Frame protection cover / Machine-welded steel frame, epoxy coated
Variable height	Steel column

TYPE

Variable height type	PI-Type
Type of engine	Electric
Type of brake	Individual brake

BASE

Type of footing	Castor - Double roller
Wheels diameter	125 mm

INCLINATIONS

Backrest	(2 gas spring) 0 to 80°
Reverse Trendelenburg	15°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Examination towel dispenser head end

COLORS

Mattress filling	Range of colors Valencia

REGULATION

Medical device class	Class I
CE marking	Yes
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M2 standard / M1 optional

ADDITIONAL INFORMATION

Comment	Remote control for electric functions

065 | FI | RBG



OUR EXCLUSIVES

EASY MOV'® EASY CLEAN® EASY CLIP®

HIGHLIGHTS

- Double column stability
- Comfort
- Patient safety

CE MD

Technical specifications

WEIGHT - ECO-PERFORMANCE

Weight	85 kg

DIMENSIONS

Length	205 cm
Width	75 / 84 with option centralized brake system cm
Length sleeping surface	200 cm
Width sleeping surface	75 cm
Variable height minimum	With castors diameter 125 mm: 47 / With castors diameter 150 mm: 49 cm
Variable height maximum	With castors diameter 125 mm: 87 / With castors diameter 150 mm: 89 cm
Ground Clearance	2,3 (castor diameter 125 mm) / 4,1 (castor diameter 150 mm) cm
Dimensions (cm)	Backrest 65 x 69 cm cm
Mattress thickness	6,5 (5 cm foam + 1,5 cm wood) cm

LYING SURFACE

Lying surface - Material	Resilience foam on wooden base

MATERIAL & COATING

Material Foam	Resilience foam
Foam HR density	35 kg/m3
Material Cover	Seamless finish, vinyl coating antibacterial
Frame	Frame protection cover / Machine-welded steel frame, epoxy coated
Variable height	Steel column

TYPE

Variable height type	PI-Type
Type of engine	Electric
Type of brake	Individual brake

BASE

Type of footing	Castor - Double roller
Wheels diameter	125 mm

INCLINATIONS

Backrest	(2 gas spring) 0 to 80°
Reverse Trendelenburg	15°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Examination towel dispenser head end

COLORS

Mattress filling	Range of colors Valencia

REGULATION

Medical device class	Class I
CE marking	Yes
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M2 standard / M1 optional

ADDITIONAL INFORMATION

Comment	Remote control for electric functions

075 | FI | RBG



OUR EXCLUSIVES

EASY MOV' ® EASY CLEAN ® EASY CLIP ®

HIGHLIGHTS

- Double column stability
- Comfort
- Patient safety

CE MD