# Technical specifications

## AMB7-S06P54-S800

**STRETCHER BED AMB7 CLAVIA LSA - WIDTH 65 - CENTRALIZED BRAKING WITH 5TH CASTOR - COMFORT MATTRESS - TECH SIDERAILS**

### PACK - EQUIPMENT

| | |
|---|---|
| Side Rails | Plastic with 2-position assistance, high for safety and low for easy access |
| Mattress | Removable comfort mattress |
| Equipment | 2 Push bars - Bumpers on 4 corners with holder for accessories |

### WEIGHT - ECO-PERFORMANCE

| | |
|---|---|
| Weight | 105 kg |

### DIMENSIONS

| | |
|---|---|
| Length | Chair position: 160 / Lying position: 219 cm cm |
| Width | 78,5 cm |
| Length sleeping surface | 202 cm |
| Width sleeping surface | 65 cm |
| Variable height minimum | Sleeping surface without mattress: 47 cm |
| Variable height maximum | Sleeping surface without mattress: 85 cm |
| Ground Clearance | 4 cm |
| Dimensions (cm) | Backrest 80 cm cm |
| Mattress thickness | 10 cm |
| Side rails height | 37 cm |
| Side rails length | 94 cm |
| Side rails thickness | 6 cm |
| Height of the push handle | Chair position: de 70 à 105 cm |
| Push bar length | 40 cm |
| Push bar diameter | 3 cm |

### MATERIAL & COATING

| | |
|---|---|
| Material Foam | Hight resilience foam |
| Foam HR density | 35 kg/m3 |
| Material Cover | Techmaflex fabric |
| Frame | Plastic protection cover / Steel epoxy structure |
| Variable height | Steel column |

### TYPE

| | |
|---|---|
| Type of mattress | Standard Comfort |
| Class Mattress | Class 0 |
| Variable height type | Electric |
| Type of engine | PI-Type |
| Type of brake | Centralized brake system with 5th directional wheel |

### BASE

| | |
|---|---|
| Type of footing | Castor - Double roller |
| Wheels diameter | 150 mm |

### MOBILITY

| | |
|---|---|
| Type of battery | Lithium-Ion 2,5A (50 cycles) |
| Charging time | about 10 heure |
| Consumption at rest | 0,5 (120/230V) |
| Consumption in function | on maximum connected 12A - on maximum battery 15A |
| Consumption in charge | 1A |

### INCLINATIONS

| | |
|---|---|
| Backrest | 0 to 78° |
| Legrest | 0 to 54° |
| Reverse Trendelenburg | 10° |
| Trendelenburg | 15° |

### SAFETY CHARGE

| | |
|---|---|
| Maximum patient weight | 185 kg |
| SWL | 250 kg |

### CONFIGURATION

| | |
|---|---|
| Configuration | Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest / 2 section backrest with a removable head section to fasten a surgery head rest for ophthalmology, stomatology and ENT |
| Number of IV pole support | 2 slots on the seat |

### REGULATION

| | |
|---|---|
| Medical device class | Class I |
| CE marking | CE |
| European regulation (UE 2017/745) | Yes |

### FIRE CLASSIFICATION

| | |
|---|---|
| Mattress cover | M1 |
| Vegetable fibers | M1 |

### ADDITIONAL INFORMATION

| | |
|---|---|
| Comment | 6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR |




## OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · TECH+ SIDE RAILS® · EASY CLIP®

## HIGHLIGHTS

- Pre-programmed functions
- Optimizing space
- Interchangeability
- Traceability

CE MD

# Technical specifications

## AMB7-S07P54-S800

**STRETCHER BED AMB7 CLAVIA LSA - WIDTH 75 - CENTRALIZED BRAKING WITH 5TH CASTOR - COMFORT MATTRESS - TECH SIDERAILS**

### PACK - EQUIPMENT

| | |
|---|---|
| Side Rails | Plastic with 2-position assistance, high for safety and low for easy access |
| Mattress | Removable comfort mattress |
| Equipment | 2 Push bars - Bumpers on 4 corners with holder for accessories |

### WEIGHT - ECO-PERFORMANCE

| | |
|---|---|
| Weight | 107 kg |

### DIMENSIONS

| | |
|---|---|
| Length | Chair position: 160 / Lying position: 219 cm cm |
| Width | 88,5 cm |
| Length sleeping surface | 202 cm |
| Width sleeping surface | 75 cm |
| Variable height minimum | Sleeping surface without mattress: 47 cm |
| Variable height maximum | Sleeping surface without mattress: 85 cm |
| Ground Clearance | 4 cm |
| Dimensions (cm) | Backrest 80 cm cm |
| Mattress thickness | 10 cm |
| Side rails height | 37 cm |
| Side rails length | 94 cm |
| Side rails thickness | 6 cm |
| Height of the push handle | Chair position: de 70 à 105 cm |
| Push bar length | 40 cm |
| Push bar diameter | 3 cm |

### MATERIAL & COATING

| | |
|---|---|
| Material Foam | Hight resilience foam |
| Foam HR density | 35 kg/m3 |
| Material Cover | Techmaflex fabric |
| Frame | Plastic protection cover / Steel epoxy structure |
| Variable height | Steel column |

### TYPE

| | |
|---|---|
| Type of mattress | Standard Comfort |
| Class Mattress | Class 0 |
| Variable height type | Electric |
| Type of engine | PI-Type |
| Type of brake | Centralized brake system with 5th directional wheel |

### BASE

| | |
|---|---|
| Type of footing | Castor - Double roller |
| Wheels diameter | 150 mm |

### MOBILITY

| | |
|---|---|
| Type of battery | Lithium-Ion 2,5A (50 cycles) |
| Charging time | about 10 heure |
| Consumption at rest | 0,5 (120/230V) |
| Consumption in function | on maximum connected 12A - on maximum battery 15A |
| Consumption in charge | 1A |

### INCLINATIONS

| | |
|---|---|
| Backrest | 0 to 78° |
| Legrest | 0 to 54° |
| Reverse Trendelenburg | 10° |
| Trendelenburg | 15° |

### SAFETY CHARGE

| | |
|---|---|
| Maximum patient weight | 185 kg |
| SWL | 250 kg |

### CONFIGURATION

| | |
|---|---|
| Configuration | Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest / 2 section backrest with a removable head section to fasten a surgery head rest for ophthalmology, stomatology and ENT |
| Number of IV pole support | 2 slots on the seat |

### REGULATION

| | |
|---|---|
| Medical device class | Class I |
| CE marking | CE |
| European regulation (UE 2017/745) | Yes |

### FIRE CLASSIFICATION

| | |
|---|---|
| Mattress cover | M1 |
| Vegetable fibers | M1 |

### ADDITIONAL INFORMATION

| | |
|---|---|
| Comment | 6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR |




## OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · TECH+ SIDE RAILS® · EASY CLIP®

## HIGHLIGHTS

- Pre-programmed functions
- Optimizing space
- Interchangeability
- Traceability

CE MD