Technical specifications

AMB7-A06P54-S800

SURGERY STRETCHER BED AMB7 CLAVIA LCA - WIDTH 65 - CENTRALIZED BRAKING WITH 5TH CASTOR - MATTRESS - TECH SIDERAILS

PACK - EQUIPMENT

Side Rails	Plastic with 2-position assistance, high for safety and low for easy access
Mattress	Removable comfort mattress
Equipment	2 Push bars - Bumpers on 4 corners with holder for accessories

WEIGHT - ECO-PERFORMANCE

Weight	90 kg

DIMENSIONS

Length	Chair position: 156 / Lying position (standard headrest) : 202 / Lying position (ophtalmo headrest) : 221 cm cm
Width	78,5 cm
Length sleeping surface	202 cm
Width sleeping surface	65 cm
Variable height minimum	Sleeping surface without mattress: 47 cm
Variable height maximum	Sleeping surface without mattress: 85 cm
Ground Clearance	4 cm
Dimensions (cm)	Backrest 80 cm cm
Mattress thickness	10 cm
Side rails height	37 cm
Side rails length	94 cm
Side rails thickness	6 cm
Height of the push handle	Chair position: de 70 à 105 cm
Push bar length	40 cm
Push bar width	3 cm
Push bar diameter	3 cm

MATERIAL & COATING

Material Foam	Hight resilience foam
Foam HR density	35 kg/m3
Material Cover	Techmaflex fabric
Frame	Plastic protection cover / Steel epoxy structure
Variable height	Steel column
Material	Plastic side rails

TYPE

Type of mattress	Standard Comfort
Class Mattress	Class 0
Variable height type	Electric
Type of engine	PI-Type
Type of brake	Centralized brake system with 5th directional wheel

BASE

Type of footing	Castor - Double roller
Wheels diameter	150 mm

MOBILITY

Type of battery	Lithium-Ion 2,5A (50 cycles)
Charging time	about 10 heure
Consumption at rest	0,5 (120/230V)
Consumption in function	on maximum connected 12A - on maximum battery 15A
Consumption in charge	1A

INCLINATIONS

Backrest	0 to 78°
Legrest	0 to 54°
Reverse Trendelenburg	10°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest
Number of IV pole support	2 slots on the seat

REGULATION

Medical device class	Class I
CE marking	CE
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M1
Vegetable fibers	M1

ADDITIONAL INFORMATION

Comment	6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR



OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · SMART HEAD REST® · TECH+ SIDE RAILS®

HIGHLIGHTS

- Equipment
- Universal support
- Easy Clip
- Interchangeability
- Traceability

CE MD

Technical specifications

AMB7-A06P54-S801

SURGERY STRETCHER BED AMB7 CLAVIA LCA - WIDTH 65 - CENTRALIZED BRAKING WITH 5TH CASTOR - MATTRESS - WITHOUT HEADREST

PACK - EQUIPMENT

Side Rails	Plastic with 2-position assistance, high for safety and low for easy access
Mattress	Removable comfort mattress
Equipment	2 Push bars - Bumpers on 4 corners with holder for accessories

WEIGHT - ECO-PERFORMANCE

Weight	90 kg

DIMENSIONS

Length	Chair position: 156 / Lying position (standard headrest) : 202 / Lying position (ophtalmo headrest) : 221 cm cm
Width	78,5 cm
Length sleeping surface	202 cm
Width sleeping surface	65 cm
Variable height minimum	Sleeping surface without mattress: 47 cm
Variable height maximum	Sleeping surface without mattress: 85 cm
Ground Clearance	4 cm
Dimensions (cm)	Backrest 80 cm cm
Mattress thickness	10 cm
Side rails height	37 cm
Side rails length	94 cm
Side rails thickness	6 cm
Height of the push handle	Chair position: de 70 à 105 cm
Push bar length	40 cm
Push bar width	3 cm
Push bar diameter	3 cm

MATERIAL & COATING

Material Foam	Hight resilience foam
Foam HR density	35 kg/m3
Material Cover	Techmaflex fabric
Frame	Plastic protection cover / Steel epoxy structure
Variable height	Colonne métallique
Material	Plastic side rails

TYPE

Type of mattress	Standard Comfort
Class Mattress	Class 0
Variable height type	Electric
Type of engine	PI-Type
Type of brake	Centralized brake system with 5th directional wheel

BASE

Type of footing	Castor - Double roller
Wheels diameter	150 mm

MOBILITY

Type of battery	Lithium-Ion 2,5A (50 cycles)
Charging time	about 10 heure
Consumption at rest	0,5 (120/230V)
Consumption in function	on maximum connected 12A - on maximum battery 15A
Consumption in charge	1A

INCLINATIONS

Backrest	0 to 78°
Legrest	0 to 54°
Reverse Trendelenburg	10°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest / 2 section backrest with a removable head section to fasten a surgery head rest for ophthalmology, stomatology and ENT
Number of IV pole support	2 slots on the seat

REGULATION

Medical device class	Class I
CE marking	CE
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M1
Vegetable fibers	M1

ADDITIONAL INFORMATION

Comment	6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR



OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · SMART HEAD REST® · TECH+ SIDE RAILS®

HIGHLIGHTS

- Equipment
- Universal support
- Easy Clip
- Interchangeability
- Traceability

CE MD

Technical specifications

AMB7-A07P54-S800

SURGERY STRETCHER BED AMB7 CLAVIA LCA - WIDTH 75 - CENTRALIZED BRAKING WITH 5TH CASTOR - MATTRESS - TECH SIDERAILS

PACK - EQUIPMENT

Side Rails	Plastic with 2-position assistance, high for safety and low for easy access
Mattress	Removable comfort mattress
Equipment	2 Push bars - Bumpers on 4 corners with holder for accessories

WEIGHT - ECO-PERFORMANCE

Weight	92 kg

DIMENSIONS

Length	Chair position: 156 / Lying position (standard headrest) : 202 / Lying position (ophtalmo headrest) : 221 cm cm
Width	88,5 cm
Length sleeping surface	202 cm
Width sleeping surface	75 cm
Variable height minimum	Sleeping surface without mattress: 47 cm
Variable height maximum	Sleeping surface without mattress: 85 cm
Ground Clearance	4 cm
Dimensions (cm)	Backrest 80 cm cm
Mattress thickness	10 cm
Side rails height	37 cm
Side rails length	94 cm
Side rails thickness	6 cm
Height of the push handle	Chair position: de 70 à 105 cm
Push bar length	40 cm
Push bar width	3 cm
Push bar diameter	3 cm

MATERIAL & COATING

Material Foam	Hight resilience foam
Foam HR density	35 kg/m3
Material Cover	Techmaflex fabric
Frame	Plastic protection cover / Steel epoxy structure
Variable height	Steel column
Material	Plastic side rails

TYPE

Type of mattress	Standard Comfort
Class Mattress	Class 0
Variable height type	Electric
Type of engine	PI-Type
Type of brake	Centralized brake system with 5th directional wheel

BASE

Type of footing	Castor - Double roller
Wheels diameter	150 mm

MOBILITY

Type of battery	Lithium-Ion 2,5A (50 cycles)
Charging time	about 10 heure
Consumption at rest	0,5 (120/230V)
Consumption in function	on maximum connected 12A - on maximum battery 15A
Consumption in charge	1A

INCLINATIONS

Backrest	0 to 78°
Legrest	0 to 54°
Reverse Trendelenburg	10°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest
Number of IV pole support	2 slots on the seat

REGULATION

Medical device class	Class I
CE marking	CE
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M1
Vegetable fibers	M1

ADDITIONAL INFORMATION

Comment	6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR



OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · SMART HEAD REST® · TECH+ SIDE RAILS®

HIGHLIGHTS

- Equipment
- Universal support
- Easy Clip
- Interchangeability
- Traceability

CE MD

Technical specifications

AMB7-A07P54-S801

SURGERY STRETCHER BED AMB7 CLAVIA LCA - WIDTH 75 - CENTRALIZED BRAKING WITH 5TH CASTOR - MATTRESS - WITHOUT HEADREST

PACK - EQUIPMENT

Side Rails	Plastic with 2-position assistance, high for safety and low for easy access
Mattress	Removable comfort mattress
Equipment	2 Push bars - Bumpers on 4 corners with holder for accessories

WEIGHT - ECO-PERFORMANCE

Weight	92 kg

DIMENSIONS

Length	Chair position: 156 / Lying position (standard headrest) : 202 / Lying position (ophtalmo headrest) : 221 cm cm
Width	88,5 cm
Length sleeping surface	202 cm
Width sleeping surface	75 cm
Variable height minimum	Sleeping surface without mattress: 47 cm
Variable height maximum	Sleeping surface without mattress: 85 cm
Ground Clearance	4 cm
Dimensions (cm)	Backrest 80 cm cm
Mattress thickness	10 cm
Side rails height	37 cm
Side rails length	94 cm
Side rails thickness	6 cm
Height of the push handle	Chair position: de 70 à 105 cm
Push bar length	40 cm
Push bar width	3 cm
Push bar diameter	3 cm

MATERIAL & COATING

Material Foam	Hight resilience foam
Foam HR density	35 kg/m3
Material Cover	Techmaflex fabric
Frame	Plastic protection cover / Steel epoxy structure
Variable height	Steel column
Material	Plastic side rails

TYPE

Type of mattress	Standard Comfort
Class Mattress	Class 0
Variable height type	Electric
Type of engine	PI-Type
Type of brake	Centralized brake system with 5th directional wheel

BASE

Type of footing	Castor - Double roller
Wheels diameter	150 mm

MOBILITY

Type of battery	Lithium-Ion 2,5A (50 cycles)
Charging time	about 10 heure
Consumption at rest	0,5 (120/230V)
Consumption in function	on maximum connected 12A - on maximum battery 15A
Consumption in charge	1A

INCLINATIONS

Backrest	0 to 78°
Legrest	0 to 54°
Reverse Trendelenburg	10°
Trendelenburg	15°

SAFETY CHARGE

Maximum patient weight	185 kg
SWL	250 kg

CONFIGURATION

Configuration	Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest / 2 section backrest with a removable head section to fasten a surgery head rest for ophthalmology, stomatology and ENT
Number of IV pole support	2 slots on the seat

REGULATION

Medical device class	Class I
CE marking	CE
European regulation (UE 2017/745)	Yes

FIRE CLASSIFICATION

Mattress cover	M1
Vegetable fibers	M1

ADDITIONAL INFORMATION

Comment	6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR



OUR EXCLUSIVES

SOFT SOUND® · EASY MOV'® · SMART HEAD REST® · TECH+ SIDE RAILS®

HIGHLIGHTS

- Equipment
- Universal support
- Easy Clip
- Interchangeability
- Traceability

CE MD