

PACK - EQUIPMENT

Equipment Retractable armrests with multidirectional adjustment 55 x 17 cm

WEIGHT - ECO-PERFORMANCE

Weight 108 kg

DIMENSIONS

Length Chair position: 156 /Lying position: 214 cm
 Width 115 cm
 Length sleeping surface 213 cm
 Width sleeping surface 73 cm
 Variable height minimum Sleeping surface without mattress: 47 cm
 Variable height maximum Sleeping surface without mattress: 85 cm
 Ground Clearance 4 cm
 Dimensions (cm) Backrest 80 cm cm
 Mattress thickness 12 cm

ARMRESTS

Length 55 mm
 Width 17 mm
 Thickness 6 cm
 Height armrests from the seat Varies according to the backrest angle, from 0 to 27 0 à 27 mm

LYING SURFACE

Bedbase - Material Steel epoxy
 Lying surface - Material CDF

MATERIAL & COATING

Material Foam Hight resilience foam
 Foam HR density 37 kg/m³
 Viscoelastic foam density 40 kg/m³
 Material Cover Techmaflex fabric
 Frame Plastic protection cover / Steel epoxy structure
 Variable height Steel column

TYPE

Variable height type Electric
 Type of engine PI-Type
 Type of brake Individual braking system

BASE

Type of footing Castor - Simple roller
 Wheels diameter 125 mm

INCLINATIONS

Backrest 0 to 78°
 Legrest 0 to 54°
 Reverse Trendelenburg 10°
 Trendelenburg 15°

SAFETY CHARGE

Maximum patient weight 200 kg
 SWL 250 kg

PROTECTION SIGN

Engines IP66

CONFIGURATION

Configuration Electrical variable height / Electric backward tilt function / Electric backrest with emergency cpr / Electric legrest

REGULATION

Medical device class Class I
 CE marking CE
 European regulation (UE 2017/745) Yes

FIRE CLASSIFICATION

Mattress cover M1

ADDITIONAL INFORMATION

Comment 6 programmed positions: Welcome, Relax, Reverse Trend, Secured Trendelenburg position, CPR



OUR EXCLUSIVES



HIGHLIGHTS

- Lying surface
- Elevation system
- Configurable
- Easy Clip
- Easy CLEAN
- Interchangeability
- Traceability

