Technical specifications

PP-S10015-CIRV1

TRANSFER CABINET - STOCKALLI M3 - F1200 - WITH FACING - EQUIPPED V1



15G

WEIGHT - ECO-PERFORMANCE

Weight bare structure	70,2 kg
Total Weight - Pack	99 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	137 cm
Depth	43,8 cm
Front	F1200
Height	149,9 cm
Thickness	Sides, Back, Bottom: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

PP-S60015-CIRV1

TRANSFER CABINET - STOCKALLI M3 - F600 15G - WITH SIDE - EQUIPPED V1

WEIGHT - ECO-PERFORMANCE

Weight bare structure	20,9 kg
Total Weight - Pack	36,8 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	85,3 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

PP-S60015-CIRV2

TRANSFER CABINET - STOCKALLI M3 - F600 15G - WITH SIDE - EQUIPPED V2

WEIGHT - ECO-PERFORMANCE

Weight bare structure	20,9 kg
Total Weight - Pack	38,1 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	85,3 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

PP-S60015-CIRV3

TRANSFER CABINET - STOCKALLI M3 - F600 15G - WITH FACING - EQUIPPED V3

WEIGHT - ECO-PERFORMANCE

Weight bare structure	34,3 kg
Total Weight - Pack	52,7 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	85,3 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm
Thickness	Sides, Back, Roof : 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	2 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

15G



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

PP-S62015-CIRV1

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF600 15G - WITH SIDE - EQUIPPED V1

WEIGHT - ECO-PERFORMANCE

Weight bare structure	28 kg
Total Weight - Pack	59,8 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	149,3 cm
Depth	43,8 cm
Front	2F600
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	6 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

15G



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

PP-S62015-CIRV2

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF600 15G - EQUIPPED V2

WEIGHT - ECO-PERFORMANCE

Weight bare structure	49,7 kg
Total Weight - Pack	82,5 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	149,3 cm
Depth	43,8 cm
Front	2F600
Height	149,9 cm
Thickness	Sides, Back, Roof : 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	6 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

15G



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S10015-CIRV2

TRANSFER CABINET - STOCKALLI M3 - F1200 15G - WITH SIDE - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	57 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	137 cm
Depth	43,8 cm
Front	F1200
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Glissière amovible sans outils

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S40015-CIR

TRANSFER CABINET - STOCKALLI M3 - F400 15G - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	18,6 kg

DIMENSIONS

Width	66 cm
Depth	62,8 cm
Front	F400
Height	149,9 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	2 guide handle on each side

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S40015-CIRV1

TRANSFER CABINET - STOCKALLI M3 - F400 15G - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	40,6 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	57,1 cm
Depth	62,8 cm
Front	F400
Height	149,9 cm
Thickness	Sides, Back, Bottom, Roof: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	2 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

15G



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S42015-CIR

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF400 15G - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	28,4 kg

DIMENSIONS

Width	110 cm
Depth	62,8 cm
Front	2F400
Height	149,9 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	2 guide handle on each side

COLORS

Box	Black

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S42015-CIRV1

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF400 15G - WITH FACING - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	55,7 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	101,2 cm
Depth	62,8 cm
Front	F400
Height	149,9 cm
Thickness	Sides, Back, Bottom, Roof: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	6 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	2 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S42015-CIRV2

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF400 15G - WITH SIDE - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	35,2 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	101,2 cm
Depth	62,8 cm
Front	2F400
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	6 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	2 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S60015-CIR

TRANSFER CABINET - STOCKALLI M3 - F600 15G - TO BE EQUIPPED



15G

WEIGHT - ECO-PERFORMANCE

Weight bare structure	16,1 kg

DIMENSIONS

Width	85,5 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Black

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S60015-CIRV1

TRANSFER CABINET - STOCKALLI M3 - F600 15G - WITH FACING - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	34,3 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	85,3 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm
Thickness	Sides, Back, Bottom, Roof: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S60015-CIRV2

TRANSFER CABINET - STOCKALLI M3 - F600 15G - WITH SIDE - TO BE EQUIPPED



15G

WEIGHT - ECO-PERFORMANCE

Weight bare structure	20,9 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	85,3 cm
Depth	43,8 cm
Front	F600
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	125 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	15
Sliders: ABS tray height 50 mm	20
Sliders: Shelf for Daily pillboxes medium model height 50 mm	21

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S62015-CIR

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF600 15G - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	23,2 kg

DIMENSIONS

Width	149,5 cm
Depth	43,8 cm
Front	2F600
Height	149,9 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Black

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2

15G



OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S62015-CIRV1

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF600 15G - WITH FACING - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	49,7 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	149,3 cm
Depth	43,8 cm
Front	2F600
Height	149,9 cm
Thickness	Sides, Back, Bottom, Roof: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Top	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV

Technical specifications

MO-S62015-CIRV2

DOUBLE TRANSFER CABINET - STOCKALLI M3 - 2XF600 15G - WITH SIDE - TO BE EQUIPPED

WEIGHT - ECO-PERFORMANCE

Weight bare structure	28 kg
Plant-based pourcentage (on total weight)	65%
Percentage of recycled material	15%

DIMENSIONS

Width	149,3 cm
Depth	43,8 cm
Front	2F600
Height	149,9 cm
Thickness	Sides: 0,6 cm

TYPE

Type of brake	Individual brake on the front castors

MATERIAL & COATING

Frame	Welded steel - Volcanic Black Epoxy
Box	Vegetable fibers
Handles	PA6 with glass fibers
Wheels	Thermoplastic rubber, grey non-marking
Internal runner walls / Slides	PA6 with glass fibers

BASE

Type of footing	4 swivel wheels with 2 braked at the front
Wheels diameter	125 mm

TYPE OF ATTACHMENT

Internal runner walls / Slides	Removable slide without tools

SAFETY CHARGE

Maximum admissible load	250 kg

CONFIGURATION

Configuration	1 guide handle on each side

COLORS

Box	Quartz

CAPACITY

Slides number (G height)	2 x 15G
Typ of springers	Sliders
Sliders: Drawer height 75 mm	30
Sliders: ABS tray height 50 mm	40
Sliders: Shelf for Daily pillboxes medium model height 50 mm	42

FIRE CLASSIFICATION

Plastic	M2
Vegetable fibers	D-s2d0



15G

OUR EXCLUSIVES

P20®

EASY CLEAN®

HIGHLIGHTS

- Easy MOV